

# Technical Specification: Thermo-rewrite Printer

## ESL CARD System S-2 series



S-2 can be print on LEUCO, REWRITE and THERMAL cards.

### High performance card system

The quickest card processing time in the industry, 2.8 seconds.  
allowing prompt operation at the cash-register and smooth shopping by customers.  
Three types of cards are usable.  
Three types, i.e., thermal, rewrite and Leuco cards, can be handled.  
Large liquid crystal display is used.  
Size: 160~64 dot  
Simple operation, using configurable function keys.

### (Options)

Memory cards (memory cards of 2 mega-bits allows the capture of vital customer information for CRM usage)  
Built-in modem are available.  
IC cards are to be applicable (contact type, 0.76 in thickness)

Speedy response to the customers, without hindering sales operation.

Size	121mm(width) x 210mm(height) x 351mm(length)
Weight	3.8 kg
Applicable card	Thermal / rewrite / Leuco
Processing time	2.8 seconds (minimum)
Memory cards	Memory capacity : 2 mega-bits
Display	LCD display unit (operator side): 10 digits and 6 lines. LED display unit (customer side): 7 segments
Keyboard	20 keys (mode of silicon rubber)
External Interface	RS-232C plus modem
Power Supply	AC 100V / 220V 50 /60 Hz

